

A30 & A30HP "Rockmaster" Pumps

Trailer Mounted Concrete Pumps

Additional Features:

- Variable Displacement Pump (A30HP only)
- Weatherproof NEMA 4 control panel
- Reversibility at any point in the stroke
- High capacity hydraulic oil cooler
- Variable volume output
- Highway rated axle
- Electric brakes
- Fenders and flush-mounted tail-lights
- Adjustable pintle hitch
- Hopper grate
- Safety emergency stop function
- Steel pistons with urethane cups
- Hard chromed concrete cylinders
- Hour meter
- Splined shaft on "S" Valve
- Dual hydraulic circuit
- Highest standard horsepower and concrete pressure in class

Optional Features:

- Chrome wheels
- Radio remote control
- 7-function hardwire remote control (On/Off/Reverse/E-stop/Horn-reset/RPM/Stroke Change)

MODEL		A30	A30HP
Concrete Output	yd ³ /hr	30	30
	m ³ /hr	23	23
Concrete Pressure	psi	903	903
	bar	62	62
Perkins Diesel Engine	hp	82	82
	kW	61	61
Main Hydraulic Pump	Gear Pump		Variable Displacement Pump
Concrete Cylinder Diameter	in	5"	5"
	mm	127	127
Stroke Length	in	30"	30"
	mm	762	762
Maximum Aggregate Size	in	1	1
	mm	25	25
Hopper Capacity	ft ³	10	10
	liters	283	283
Hopper Height	in	40	40
	mm	1016	1016
Hydraulic Oil Capacity	gal	40	40
	liters	151	151
Fuel Capacity	gal	29	29
	liters	110	110
Outlet Size	in	5	5
	mm	127	127
Dimensions	Length	Width	Height
	in 156	61	64
	mm 3962	1549	1626
Weight (Approx.)	lbs	4460	4460
	kg	2023	2023

Maximum theoretical performance shown above. Maximum output and pressure cannot be reached simultaneously. Performance will vary depending on slump, mix design and pipeline diameter. Specifications subject to change without prior notice.